



naturally adaptive.



SMART-SIZED HIGH SPEED DISPENSER

Introducing - The Spider - PCB design freedom. State of the art technology, easily integrated in any line.



CELL SOLUTION

dispense technology.

- Up to 2 valves simultaneously
- 5 different valves, large application range

productivity.

- Up to 150'000 dots/h (with Piezo Jet Valve)
- Up to 2'000'000 dot/h line mode

small footprint

- Requires only 1 m² of production floor
- Machine fits through 90 cm wide door

mineral cast.

- No vibration, symmetrical mineral casting
- No warpage, no thermal drift

laser height mapping

- Mapping of heights using laser technology
- Compensation of substrate warp / 3D contour

linear motors


- Fast, reliable double drive linear motors
- No maintenance, longest lifetime

naturally adaptive.

INTEGRATE INTO HIGH SPEED LINES AND HIGHLY COMPLEX DISPENSE APPLICATIONS



Versatile range of dispensing applications such as Solder Paste and SMT Glue, LED Encapsulation, Silver Epoxy, Dam and Fill, Underfill, Cavity Fill, 2.5D Dispensing via laser height mapping & more



Full operator support - Automated error analysis & KPI. Training, support and troubleshooting via advanced remote access. Investment protection; all options and heads retrofittable.



Two processes at the same time. Plug and Play for valve change. Piezo Jet Valve - super high speed for low viscosity. Dynamic Shockwave, Volume Displacement, Time/Pressure, Archimedean Screw Valve





MULTITALENT SOFTWARE AT YOUR FINGERTIPS State of the art, full graphics, 21.5" 16:9 touch screen, Windows 10 - 64 bit, fingertip operation, real time visualization zoom at camera windows, all-in-one job planning, universal CAD conversion, setup optimization, easy definition of pattern and guided process support

optional.

Valves & Pumps Media Heating

Level Detection

Process Control











Needle and jet heating system

Automatic syringe level detection

Process control adjustment & stabilization

Vacuum Cleaning Station, High Precision Scale, Clean Room, Heating/Vacuum Table Full process control meeting automotive standards and more







naturally adaptive.

S	ler.

			•	
	Process	Max. dispensing speed	Piezo Jet: 150'000 dots/h Pneumatic Jet: 80'000 dots/h	Time/Pressure: 28'000 dots/h Archimedean Screw: 24'000 dots/h
		Dispensing mode	Dot, line, curve, interpolated 3D contour	
	Accuracy	Placement XY dots	40 μm (3σ)	
		Positioning Z axis	20 μm (3σ)	
	PCB	PCB dimensions	50 x 50 mm up to 406 x 305 mm	1 (2 x 2" up to 16 x 12")
	Dimensions	Machine footprint	880 x 1090 mm (34.7 x 43")	



Wildlife consistently shows us with breathtaking flexibility how nature can adapt itself to the many different demands of its environment; that is what inspires us! Essemtec AG is a privately owned company with its development and production site in Switzerland. The product portfolio comprises of production equipment for electronic assembly and more. Our high tech solutions can be adjusted quickly and easily to meet wide ranging requirements; we are therefore able to respond to all manner of customer requests. That's why "naturally adaptive" is our motto across all ranges.

Disclaimer & Copyright:

Information in this brochure is for general information purpose only. Further details are provided in the specification sheet. All materials contained in this brochure are copyright © Essemtec AG, Switzerland, March 2022.

Switzerland Essemtec AG

Mosenstrasse 20 CH-6287 Aesch/LU Tel: +41 41 919 60 60 info@essemtec.com

Germany Essemtec GmbH


Oskar-Messter-Strasse 25 DE-85737 Ismaning Tel: +49 893 803 55 15 info@essemtec.com

France Essemtec SAS

50, Avenue d'Alsace FR-68000 Colmar Tel: +49 172 287 56 04 info@essemtec.com

America Essemtec USA LLC

300 5th Ave Waltham, MA 02451 Tel: +1 856 218 11 31 sales-usa@essemtec.com





essemlec.com